

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture 6304 FLAT BLACK - HIGH TEMP

Registration number -

Synonyms None.

Product code 1A51H200

Issue date 15-January-2018

Version number 01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Stove paint.

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name FORREST Paint Co. DBA Forrest Technical Coatings

Address 1011 McKinley Street

P.O. Box 22110

United States

Division

Telephone 1 (541) 342-1821

e-mail info@forrestpaint.com

Contact person Not available.

1.4. Emergency telephone number (CHEMTREC -Contract # 8730) 1 (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification F+;R12, Carc. Cat. 2;R45, Repr. Cat. 3;R63, Xn;R48/20, Xi;R36, R66-67

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

| | | |
|----------|------------|---|
| Aerosols | Category 2 | H223 - Flammable aerosol. H229 - Pressurized container: May burst if heated. |
|----------|------------|---|

| | | |
|----------------------|----------------|--|
| Gases under pressure | Compressed gas | H280 - Contains gas under pressure; may explode if heated. |
|----------------------|----------------|--|


Health hazards

| | | |
|--|-------------------------------------|--|
| Acute toxicity, oral | Category 4 | H302 - Harmful if swallowed. |
| Acute toxicity, dermal | Category 4 | H312 - Harmful in contact with skin. |
| Skin corrosion/irritation | Category 2 | H315 - Causes skin irritation. |
| Serious eye damage/eye irritation | Category 2 | H319 - Causes serious eye irritation. |
| Reproductive toxicity (the unborn child) | Category 2 | H361d - Suspected of damaging the unborn child. |
| Specific target organ toxicity - single exposure | Category 3 narcotic effects | H336 - May cause drowsiness or dizziness. |
| Specific target organ toxicity - repeated exposure | Category 2 (central nervous system) | H373 - May cause damage to organs (central nervous system) through prolonged or repeated exposure. |

| | | |
|--|---|---|
| Aspiration hazard | Category 1 | H304 - May be fatal if swallowed and enters airways. |
| Environmental hazards | | |
| Hazardous to the aquatic environment, long-term aquatic hazard | Category 3 | H412 - Harmful to aquatic life with long lasting effects. |
| Hazard summary | | |
| Physical hazards | Extremely flammable. | |
| Health hazards | May cause cancer. Irritating to eyes. Also harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Occupational exposure to the substance or mixture may cause adverse health effects. | |
| Environmental hazards | Not classified for hazards to the environment. | |
| Specific hazards | Prolonged exposure may cause chronic effects. | |
| Main symptoms | Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioural changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects. | |

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

| | | |
|---------------------------------|---|--|
| Contains: | ACETONE, MANGANESE FERRITE SPINEL, Mineral spirits, N-Butyl Alcohol, Toluene, XYLENE | |
| Hazard pictograms |  | |
| Signal word | Danger | |
| Hazard statements | <p>H223 Flammable aerosol.</p> <p>H229 Pressurized container: May burst if heated.</p> <p>H280 Contains gas under pressure; may explode if heated.</p> <p>H302 Harmful if swallowed.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H312 Harmful in contact with skin.</p> <p>H315 Causes skin irritation.</p> <p>H319 Causes serious eye irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H361d Suspected of damaging the unborn child.</p> <p>H373 May cause damage to organs (central nervous system) through prolonged or repeated exposure.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p> | |
| Precautionary statements | | |
| Prevention | <p>P102 Keep out of reach of children.</p> <p>P103 Read label before use.</p> <p>P201 Obtain special instructions before use.</p> <p>P202 Do not handle until all safety precautions have been read and understood.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P260 Do not breathe mist or vapour.</p> <p>P264 Wash thoroughly after handling.</p> <p>P270 Do not eat, drink or smoke when using this product.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> | |
| Response | <p>P101 If medical advice is needed, have product container or label at hand.</p> <p>P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE/doctor.</p> <p>P330 Rinse mouth.</p> <p>P331 Do NOT induce vomiting.</p> <p>P302 + P352 IF ON SKIN: Wash with plenty of water.</p> <p>P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P308 + P313 IF exposed or concerned: Get medical advice/attention.</p> | |

P312
P332 + P313
P337 + P313
P362 + P364

Call a POISON CENTRE/doctor if you feel unwell.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.

Storage

P403 + P233
P405
P410 + P403
P412

Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Store in a well-ventilated place.
Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information

94,16 % of the mixture consists of component(s) of unknown acute oral toxicity. 90,59 % of the mixture consists of component(s) of unknown acute dermal toxicity. 62,21 % of the mixture consists of component(s) of unknown acute inhalation toxicity. 95,88 % of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 67,71 % of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment. EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

| Chemical name | % | CAS-No. / EC No. | REACH Registration No. | INDEX No. | Notes |
|--------------------------|--|------------------------|------------------------|--------------|--------|
| ACETONE | 30 - < 40 | 67-64-1 200-662-2 | - | 606-001-00-8 | # |
| Classification: | DSD: F;R11, Xi;R36, R66-67 CLP: Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336 | | | | |
| Toluene | 20 - < 30 | 108-88-3 203-625-9 | - | 601-021-00-3 | # |
| Classification: | DSD: F;R11, Repr. Cat. 3;R63, Xn;R65-48/20, Xi;R38, R67 CLP: Flam. Liq. 2;H225, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, Repr. 2;H361d, STOT RE 2;H373, Aquatic Chronic 3;H412 | | | | |
| XYLENE | 5 - < 10 | 1330-20-7 215-535-7 | - | 601-022-00-9 | # |
| Classification: | DSD: R10, Xn;R20/21, Xi;R38 CLP: Flam. Liq. 3;H226, Acute Tox. 4;H312, Skin Irrit. 2;H315, Acute Tox. 4;H332, Aquatic Chronic 3;H412 | | | | C C |
| MANGANESE FERRITE SPINEL | 1 - < 3 | 75864-23-2 - | - | - | # |
| Classification: | DSD: - CLP: STOT RE 2;H373 | | | | |
| Mineral spirits | 1 - < 3 | 8052-41-3 232-489-3 | - | 649-345-00-4 | |
| Classification: | DSD: Carc. Cat. 2;R45, Xn;R65-48/20 CLP: Flam. Liq. 3;H226, Asp. Tox. 1;H304, STOT RE 1;H372 | | | | P P |
| N-Butyl Alcohol | 1 - < 3 | 71-36-3 200-751-6 | - | 603-004-00-6 | |
| Classification: | DSD: R10, Xn;R22, Xi;R37/38-41, R67 CLP: Flam. Liq. 3;H226, Acute Tox. 4;H302, Skin Irrit. 2;H315, Eye Dam. 1;H318, STOT SE 3;H335, STOT SE 3;H336, Aquatic Chronic 3;H412 | | | | |
| Carbon Black | < 1 | 1333-86-4 215-609-9 | - | - | |
| Classification: | DSD: - CLP: Carc. 2;H351 | | | | |

| Chemical name | % | CAS-No. / EC No. | REACH Registration No. | INDEX No. | Notes |
|------------------------|--|-----------------------|------------------------|--------------|-------|
| ETHYL BENZENE | < 1 | 100-41-4 202-849-4 | - | 601-023-00-4 | # |
| Classification: | DSD: F;R11, Xn;R20-65-48/20 CLP: Flam. Liq. 2;H225, Asp. Tox. 1;H304, Acute Tox. 4;H332, Carc. 2;H351, STOT RE 2;H373, Aquatic Chronic 3;H412 | | | | |

Other components below reportable levels 30 - < 40

List of abbreviations and symbols that may be used above

DSD: Directive 67/548/EEC.

CLP: Regulation No. 1272/2008.

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all R- and H-phrases is displayed in section 16.

SECTION 4: First aid measures

General information IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Not likely, due to the form of the product. Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioural changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Flammable aerosol. Contents under pressure. Pressurised container may explode when exposed to heat or flame.

5.1. Extinguishing media

Suitable extinguishing media Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapour. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Keep combustibles (wood, paper, oil etc) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Do not breathe mist or vapour. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

| Components | Type | Value |
|------------------------------|------|-----------------------|
| ACETONE (CAS 67-64-1) | TWA | 1210 mg/m3 500 ppm |
| BUTANE (CAS 106-97-8) | STEL | 1500 mg/m3 |
| | TWA | 1200 mg/m3 |
| ETHYL BENZENE (CAS 100-41-4) | STEL | 884 mg/m3 |
| | | 200 ppm |
| | TWA | 442 mg/m3 |

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

| Components | Type | Value |
|---------------------------------|------|------------------------|
| Mineral spirits (CAS 8052-41-3) | STEL | 100 ppm 1000 mg/m3 |
| N-Butyl Alcohol (CAS 71-36-3) | TWA | 700 mg/m3 |
| | STEL | 200 mg/m3 |
| | TWA | 66 ppm 100 mg/m3 |
| PROPANE (CAS 74-98-6) | STEL | 33 ppm 1800 mg/m3 |
| | TWA | 1000 ppm 1400 mg/m3 |
| Toluene (CAS 108-88-3) | STEL | 778 ppm 384 mg/m3 |
| | TWA | 100 ppm 192 mg/m3 |
| XYLENE (CAS 1330-20-7) | STEL | 50 ppm 442 mg/m3 |
| | TWA | 100 ppm 221 mg/m3 |
| | | 50 ppm |

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

| Components | Type | Value | Form |
|---|------|-------------------------|----------------------|
| ACETONE (CAS 67-64-1) | TWA | 1210 mg/m3 500 ppm | |
| ETHYL BENZENE (CAS 100-41-4) | STEL | 884 mg/m3 | |
| | TWA | 200 ppm 442 mg/m3 | |
| MANGANESE FERRITE SPINEL (CAS 75864-23-2) | TWA | 100 ppm 0,2 mg/m3 | Inhalable fraction. |
| Toluene (CAS 108-88-3) | STEL | 0,05 mg/m3 384 mg/m3 | Respirable fraction. |
| | TWA | 100 ppm 192 mg/m3 | |
| XYLENE (CAS 1330-20-7) | STEL | 50 ppm 442 mg/m3 | |
| | TWA | 100 ppm 221 mg/m3 | |
| | | 50 ppm | |

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs) Not available.

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines
Romania OELs: Skin designation

ETHYL BENZENE (CAS 100-41-4)

Can be absorbed through the skin.

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

XYLENE (CAS 1330-20-7)

Can be absorbed through the skin.

8.2. Exposure controls
Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

| | |
|--|--|
| General information | Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. |
| Eye/face protection | Chemical respirator with organic vapour cartridge and full facepiece. |
| Skin protection | |
| - Hand protection | Wear appropriate chemical resistant gloves. |
| - Other | Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. |
| Respiratory protection | Chemical respirator with organic vapour cartridge and full facepiece. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| Hygiene measures | Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |
| Environmental exposure controls | Inform appropriate managerial or supervisory personnel of all environmental releases. |

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|---|----------------------------------|
| Appearance | Aerosol |
| Physical state | Liquid. |
| Form | Aerosol Compressed gas. |
| Colour | Black. |
| Odour | Solvent. |
| Odour threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | -187,6 °C (-305,68 °F) estimated |
| Initial boiling point and boiling range | -42,1 °C (-43,78 °F) estimated |
| Flash point | -92,0 °C (-133,6 °F) |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | 1,3 % estimated |
| Flammability limit - upper (%) | 12,8 % estimated |
| Vapour pressure | 1523,94 hPa estimated |
| Vapour density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | 0 % |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | 287,78 °C (550 °F) estimated |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Explosive properties | Not explosive. |
| Oxidising properties | Not oxidising. |

9.2. Other information

| | |
|-------------------------|---|
| Density | 6,34 lb/gal |
| Percent volatile | 90,95 %w/w |
| Specific gravity | 0,76 |
| VOC | 639,24 g/l COATING 423,47 g/l Material |

SECTION 10: Stability and reactivity

| | |
|--|---|
| 10.1. Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| 10.2. Chemical stability | Material is stable under normal conditions. |
| 10.3. Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| 10.4. Conditions to avoid | Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| 10.5. Incompatible materials | Strong acids. Acids. Strong oxidising agents. Nitrates. Halogens. Fluorine. Chlorine. |
| 10.6. Hazardous decomposition products | No hazardous decomposition products are known. |

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

| | |
|---------------------|--|
| Inhalation | May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. |
| Skin contact | Harmful in contact with skin. Causes skin irritation. |
| Eye contact | Causes serious eye irritation. |
| Ingestion | Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. |

Symptoms Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioural changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

11.1. Information on toxicological effects

| | |
|--|---|
| Acute toxicity | May be fatal if swallowed and enters airways. Harmful in contact with skin. |
| Skin corrosion/irritation | Causes skin irritation. |
| Serious eye damage/eye irritation | Causes serious eye irritation. |
| Respiratory sensitisation | Due to partial or complete lack of data the classification is not possible. |
| Skin sensitisation | Due to partial or complete lack of data the classification is not possible. |
| Germ cell mutagenicity | Due to partial or complete lack of data the classification is not possible. |
| Carcinogenicity | Risk of cancer cannot be excluded with prolonged exposure. |

IARC Monographs. Overall Evaluation of Carcinogenicity

| | |
|---------------------------------|---|
| Carbon Black (CAS 1333-86-4) | 2B Possibly carcinogenic to humans. |
| ETHYL BENZENE (CAS 100-41-4) | 2B Possibly carcinogenic to humans. |
| Mineral spirits (CAS 8052-41-3) | 3 Not classifiable as to carcinogenicity to humans. |
| Toluene (CAS 108-88-3) | 3 Not classifiable as to carcinogenicity to humans. |
| XYLENE (CAS 1330-20-7) | 3 Not classifiable as to carcinogenicity to humans. |

| | |
|---|---|
| Reproductive toxicity | Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child. |
| Specific target organ toxicity - single exposure | May cause drowsiness and dizziness. |
| Specific target organ toxicity - repeated exposure | May cause damage to organs (central nervous system) through prolonged or repeated exposure. |
| Aspiration hazard | May be fatal if swallowed and enters airways. |
| Mixture versus substance information | No information available. |
| Other information | Not available. |

SECTION 12: Ecological information

12.1. Toxicity Harmful to aquatic life with long lasting effects. Based on available data, the classification criteria are not met for hazardous to the aquatic environment, acute hazard.

| Components | | Species | Test results |
|-----------------------|------|---|------------------------------|
| ACETONE (CAS 67-64-1) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 10294 - 17704 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 4740 - 6330 mg/l, 96 hours |

| Components | Species | | Test results |
|-------------------------------|---------|---|--------------------------------|
| ETHYL BENZENE (CAS 100-41-4) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 1,37 - 4,4 mg/l, 48 hours |
| Fish | LC50 | Bluegill (Lepomis macrochirus) | 7,711 - 9,591 mg/l, 96 hours |
| | | Fathead minnow (Pimephales promelas) | 11,5 - 12,7 mg/l, 96 hours |
| N-Butyl Alcohol (CAS 71-36-3) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 1897 - 2072 mg/l, 48 hours |
| Fish | LC50 | Bluegill (Lepomis macrochirus) | 100 - 500 mg/l, 96 hours |
| Toluene (CAS 108-88-3) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 19,6 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 14,1 - 17,16 mg/l, 96 hours |
| XYLENE (CAS 1330-20-7) | | | |
| Aquatic | | | |
| Fish | LC50 | Bluegill (Lepomis macrochirus) | 10,464 - 16,114 mg/l, 96 hours |
| | | | 7,711 - 9,591 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

| | |
|-----------------|-------------|
| ACETONE | -0,24 |
| ETHYL BENZENE | 3,15 |
| Mineral spirits | 3,16 - 7,15 |
| N-Butyl Alcohol | 0,88 |
| Toluene | 2,73 |
| XYLENE | 3,12 - 3,2 |

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB assessment Not a PBT or vPvB substance or mixture.

Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|-------------------------------------|---|
| Residual waste | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| Contaminated packaging | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. |
| EU waste code | The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. |
| Disposal methods/information | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Special precautions | Dispose in accordance with all applicable regulations. |

SECTION 14: Transport information

ADR

14.1. UN number UN1950

14.2. UN proper shipping name Aerosols, flammable

14.3. Transport hazard class(es)

Class 2.1

Subsidiary risk -

Label(s) 2.1

Hazard No. (ADR) Not available.

Tunnel restriction code Not available.

14.4. Packing group Not available.

14.5. Environmental hazards No.

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number UN1950

14.2. UN proper shipping name Aerosols, flammable

14.3. Transport hazard class(es)

Class 2.1

Subsidiary risk -

Label(s) 2.1

14.4. Packing group Not available.

14.5. Environmental hazards No.

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number UN1950

14.2. UN proper shipping name Aerosols, flammable

14.3. Transport hazard class(es)

Class 2.1

Subsidiary risk -

Label(s) 2.1

14.4. Packing group Not available.

14.5. Environmental hazards No.

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number ID8000

14.2. UN proper shipping name Consumer commodity

14.3. Transport hazard class(es)

Class 9

Subsidiary risk ORM-D

14.4. Packing group Not available.

14.5. Environmental hazards No.

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

14.1. UN number UN1950

14.2. UN proper shipping name Aerosols, flammable

14.3. Transport hazard class(es)

Class 2.1

Subsidiary risk -

Label(s) 2.1

14.4. Packing group Not available.

14.5. Environmental hazards

Marine pollutant No.

EmS F-D, S-U

14.6. Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not established.

ADN; ADR; IMDG; RID



General information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

ACETONE (CAS 67-64-1)

ETHYL BENZENE (CAS 100-41-4)

Toluene (CAS 108-88-3)

Mineral spirits (CAS 8052-41-3)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Mineral spirits (CAS 8052-41-3)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ACETONE (CAS 67-64-1)

ETHYL BENZENE (CAS 100-41-4)

N-Butyl Alcohol (CAS 71-36-3)

Toluene (CAS 108-88-3)

XYLENE (CAS 1330-20-7)

| | |
|-----------------------------|--|
| Other regulations | Pregnant women should not work with the product, if there is the least risk of exposure. The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended. |
| National regulations | Follow national regulation for work with chemical agents. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended. |

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

| | |
|---|---|
| List of abbreviations | Not available. |
| References | Not available. |
| Information on evaluation method leading to the classification of mixture | The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. |
| Full text of any statements or R-phrases and H-statements under Sections 2 to 15 | <p>R10 Flammable.</p> <p>R11 Highly flammable.</p> <p>R12 Extremely flammable.</p> <p>R20 Harmful by inhalation.</p> <p>R20/21 Harmful by inhalation and in contact with skin.</p> <p>R22 Harmful if swallowed.</p> <p>R36 Irritating to eyes.</p> <p>R37/38 Irritating to respiratory system and skin.</p> <p>R38 Irritating to skin.</p> <p>R41 Risk of serious damage to eyes.</p> <p>R45 May cause cancer.</p> <p>R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.</p> <p>R63 Possible risk of harm to the unborn child.</p> <p>R65 Harmful: may cause lung damage if swallowed.</p> <p>R66 Repeated exposure may cause skin dryness or cracking.</p> <p>R67 Vapours may cause drowsiness and dizziness.</p> <p>H225 Highly flammable liquid and vapour.</p> <p>H226 Flammable liquid and vapour.</p> <p>H302 Harmful if swallowed.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H312 Harmful in contact with skin.</p> <p>H315 Causes skin irritation.</p> <p>H318 Causes serious eye damage.</p> <p>H319 Causes serious eye irritation.</p> <p>H332 Harmful if inhaled.</p> <p>H335 May cause respiratory irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H351 Suspected of causing cancer by inhalation.</p> <p>H351 Suspected of causing cancer.</p> <p>H361d Suspected of damaging the unborn child.</p> <p>H372 Causes damage to organs through prolonged or repeated exposure.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p> |
| Revision information | <p>Product and Company Identification: Product Uses</p> <p>Physical & Chemical Properties: Multiple Properties</p> <p>GHS: Classification</p> |
| Training information | Follow training instructions when handling this material. |
| Disclaimer | The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create any warranty, expressed or implied. It is the responsibility of the user to determine the applicability of this information and the suitability of the material or product for any particular purpose. |