

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture SATIN BLACK- HIGH TEMP BRUSH ON

Registration number -

Synonyms None.

Product code 62M290

Issue date 22-January-2018

Version number 01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Stove paint.

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name FORREST Paint Co. DBA Forrest Technical Coatings

Address 1011 McKinley Street
P.O. Box 22110
United States

Division

Telephone 1 (541) 342-1821

e-mail info@forrestpaint.com

Contact person Not available.

1.4. Emergency telephone number (CHEMTREC -Contract # 8730) 1 (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification F;R11, Carc. Cat. 2;R45, Muta. Cat. 2;R46, Repr. Cat. 3;R63, Xn;R20/21-48/20, Xi;R38

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids	Category 2	H225 - Highly flammable liquid and vapour.
-------------------	------------	--

Health hazards

Acute toxicity, oral	Category 4	H302 - Harmful if swallowed.
Acute toxicity, dermal	Category 4	H312 - Harmful in contact with skin.
Acute toxicity, inhalation	Category 4	H332 - Harmful if inhaled.
Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 1	H318 - Causes serious eye damage.
Carcinogenicity	Category 2	H351 - Suspected of causing cancer.
Reproductive toxicity (the unborn child)	Category 2	H361d - Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure	Category 2 (central nervous system)	H373 - May cause damage to organs (central nervous system) through prolonged or repeated exposure.

Aspiration hazard

Category 1

H304 - May be fatal if swallowed and enters airways.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard

Category 3

H412 - Harmful to aquatic life with long lasting effects.

Hazard summary

Physical hazards

Highly flammable.

Health hazards

May cause cancer. May cause heritable genetic damage. Also harmful by inhalation and in contact with skin. Irritating to skin. Also harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Occupational exposure to the substance or mixture may cause adverse health effects.

Environmental hazards

Not classified for hazards to the environment.

Specific hazards

Prolonged exposure may cause chronic effects.

Main symptoms

Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioural changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains:

2-Butoxyethanol, Carbon Black, ETHYL BENZENE, MANGANESE FERRITE SPINEL, Mineral spirits, N-Butyl Alcohol, Toluene, XYLENE

Hazard pictograms



Signal word

Danger

Hazard statements

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs (central nervous system) through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe mist or vapour.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE/doctor.
P330	Rinse mouth.
P331	Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE/doctor.
 P332 + P313 If skin irritation occurs: Get medical advice/attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.
 P370 + P378 In case of fire: Use appropriate media to extinguish.

Storage

P235 Keep cool.
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information 91,87 % of the mixture consists of component(s) of unknown acute oral toxicity. 67,72 % of the mixture consists of component(s) of unknown acute dermal toxicity. % of the mixture consists of component(s) of unknown acute inhalation toxicity. 96,39 % of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 24,8 % of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

2.3. Other hazards Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Toluene	30 - < 40	108-88-3 203-625-9	-	601-021-00-3	#
Classification:		DSD: F;R11, Repr. Cat. 3;R63, Xn;R65-48/20, Xi;R38, R67			
		CLP: Flam. Liq. 2;H225, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, Repr. 2;H361d, STOT RE 2;H373, Aquatic Chronic 3;H412			
XYLENE	20 - < 30	1330-20-7 215-535-7	-	601-022-00-9	#
Classification:		DSD: R10, Xn;R20/21, Xi;R38			C
		CLP: Flam. Liq. 3;H226, Acute Tox. 4;H312, Skin Irrit. 2;H315, Acute Tox. 4;H332, Aquatic Chronic 3;H412			C
MANGANESE FERRITE SPINEL	5 - < 10	75864-23-2	-	-	#
Classification:		DSD: -			
		CLP: STOT RE 2;H373			
N-Butyl Alcohol	3 - < 5	71-36-3 200-751-6	-	603-004-00-6	
Classification:		DSD: R10, Xn;R22, Xi;R37/38-41, R67			
		CLP: Flam. Liq. 3;H226, Acute Tox. 4;H302, Skin Irrit. 2;H315, Eye Dam. 1;H318, STOT SE 3;H335, STOT SE 3;H336, Aquatic Chronic 3;H412			
2-Butoxyethanol	1 - < 3	111-76-2 203-905-0	-	603-014-00-0	#
Classification:		DSD: Xn;R20/21/22, Xi;R36/38			
		CLP: Acute Tox. 4;H302, Acute Tox. 4;H312, Eye Irrit. 2;H319, Acute Tox. 4;H332			
AROMATIC PETROLEUM DISTILLATES	1 - < 3	64742-95-6 265-199-0	-	649-356-00-4	
Classification:		DSD: Carc. Cat. 2;R45, Muta. Cat. 2;R46, Xn;R65			P
		CLP: Flam. Liq. 3;H226, Asp. Tox. 1;H304, Aquatic Chronic 3;H412			P
Copper chromite black spinel	1 - < 3	68186-91-4 269-053-7	-	-	#
Classification:		DSD: -			
		CLP: -			
ETHYL BENZENE	1 - < 3	100-41-4 202-849-4	-	601-023-00-4	#
Classification:		DSD: F;R11, Xn;R20-65-48/20			
		CLP: Flam. Liq. 2;H225, Asp. Tox. 1;H304, Acute Tox. 4;H332, Carc. 2;H351, STOT RE 2;H373, Aquatic Chronic 3;H412			

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Mineral spirits	1 - < 3	8052-41-3 232-489-3	-	649-345-00-4	
Classification:		DSD: Carc. Cat. 2;R45, Xn;R65-48/20			P
		CLP: Flam. Liq. 3;H226, Asp. Tox. 1;H304, STOT RE 1;H372			P
Carbon Black	< 1	1333-86-4 215-609-9	-	-	
Classification:		DSD: -			
		CLP: Carc. 2;H351			

Other components below reportable levels 10 - < 20

List of abbreviations and symbols that may be used above

DSD: Directive 67/548/EEC.

CLP: Regulation No. 1272/2008.

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all R- and H-phrases is displayed in section 16.

SECTION 4: First aid measures

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion

Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioural changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

Highly flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

For emergency responders Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers.

6.4. Reference to other sections For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapour. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	STEL	246 mg/m3
	TWA	50 ppm
		98 mg/m3
AROMATIC PETROLEUM DISTILLATES (CAS 64742-95-6)	STEL	200 mg/m3
	TWA	100 mg/m3
Copper chromite black spinel (CAS 68186-91-4)	TWA	0,5 mg/m3
	ETHYL BENZENE (CAS 100-41-4)	STEL
		200 ppm

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value
	TWA	442 mg/m3 100 ppm
Mineral spirits (CAS 8052-41-3)	STEL	1000 mg/m3
	TWA	700 mg/m3
N-Butyl Alcohol (CAS 71-36-3)	STEL	200 mg/m3
	TWA	66 ppm 100 mg/m3
Toluene (CAS 108-88-3)	STEL	33 ppm 384 mg/m3
	TWA	100 ppm 192 mg/m3
XYLENE (CAS 1330-20-7)	STEL	50 ppm 442 mg/m3
	TWA	100 ppm 221 mg/m3 50 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Components	Type	Value	Form
2-Butoxyethanol (CAS 111-76-2)	STEL	246 mg/m3	
	TWA	50 ppm 98 mg/m3	
Copper chromite black spinel (CAS 68186-91-4)	TWA	20 ppm 2 mg/m3	
ETHYL BENZENE (CAS 100-41-4)	STEL	884 mg/m3	
	TWA	200 ppm 442 mg/m3	
MANGANESE FERRITE SPINEL (CAS 75864-23-2)	TWA	100 ppm 0,2 mg/m3	Inhalable fraction.
	TWA	0,05 mg/m3	Respirable fraction.
Toluene (CAS 108-88-3)	STEL	384 mg/m3 100 ppm	
	TWA	192 mg/m3 50 ppm	
XYLENE (CAS 1330-20-7)	STEL	442 mg/m3 100 ppm	
	TWA	221 mg/m3 50 ppm	

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs) Not available.

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines
Romania OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)	Can be absorbed through the skin.
AROMATIC PETROLEUM DISTILLATES (CAS 64742-95-6)	Can be absorbed through the skin.
ETHYL BENZENE (CAS 100-41-4)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.
XYLENE (CAS 1330-20-7)	Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.
Individual protection measures, such as personal protective equipment	
General information	Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Eye/face protection	Chemical respirator with organic vapour cartridge and full facepiece.
Skin protection	
- Hand protection	Wear appropriate chemical resistant gloves.
- Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	Chemical respirator with organic vapour cartridge and full facepiece.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Inform appropriate managerial or supervisory personnel of all environmental releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Colour	Black
Odour	Solvent.
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	110,6 °C (231,08 °F) estimated
Flash point	4,4 °C (40,0 °F) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1 % estimated
Flammability limit - upper (%)	12,7 % estimated
Vapour pressure	24,22 hPa estimated
Vapour density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	260 °C (500 °F) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
9.2. Other information	
Density	8,14 lb/gal
Percent volatile	76,57 %w/w

Specific gravity	0,98
VOC	746,68 g/l COATING 746,68 g/l Material

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong acids. Strong oxidising agents. Halogens.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact Harmful in contact with skin. Causes skin irritation.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Eye contact Causes serious eye damage.

Ingestion Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioural changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain.

11.1. Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Harmful if inhaled. Harmful in contact with skin.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory sensitisation Due to partial or complete lack of data the classification is not possible.

Skin sensitisation Due to partial or complete lack of data the classification is not possible.

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

2-Butoxyethanol (CAS 111-76-2)	3 Not classifiable as to carcinogenicity to humans.
Carbon Black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.
Copper chromite black spinel (CAS 68186-91-4)	3 Not classifiable as to carcinogenicity to humans.
ETHYL BENZENE (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Mineral spirits (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
XYLENE (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure May cause damage to organs (central nervous system) through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Mixture versus substance information No information available.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity Harmful to aquatic life with long lasting effects. Based on available data, the classification criteria are not met for hazardous to the aquatic environment, acute hazard.

Components		Species	Test results
2-Butoxyethanol (CAS 111-76-2)			
Aquatic			
Fish	LC50	Inland silverside (<i>Menidia beryllina</i>)	1250 mg/l, 96 hours
AROMATIC PETROLEUM DISTILLATES (CAS 64742-95-6)			
Aquatic			
Crustacea	EC50	Water flea (<i>Daphnia pulex</i>)	2,7 - 5,1 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>)	8,8 mg/l, 96 hours
			8,8 mg/l, 96 hours
ETHYL BENZENE (CAS 100-41-4)			
Aquatic			
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	1,37 - 4,4 mg/l, 48 hours
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	7,711 - 9,591 mg/l, 96 hours
		Fathead minnow (<i>Pimephales promelas</i>)	11,5 - 12,7 mg/l, 96 hours
N-Butyl Alcohol (CAS 71-36-3)			
Aquatic			
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	1897 - 2072 mg/l, 48 hours
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	100 - 500 mg/l, 96 hours
Toluene (CAS 108-88-3)			
Aquatic			
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	19,6 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>)	14,1 - 17,16 mg/l, 96 hours
XYLENE (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	10,464 - 16,114 mg/l, 96 hours
			7,711 - 9,591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

2-Butoxyethanol	0,83
ETHYL BENZENE	3,15
Mineral spirits	3,16 - 7,15
N-Butyl Alcohol	0,88
Toluene	2,73
XYLENE	3,12 - 3,2

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB Not a PBT or vPvB substance or mixture.

assessment Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1263
14.2. UN proper shipping name	Paint
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Hazard No. (ADR)	33
Tunnel restriction code	D/E
14.4. Packing group	II
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number	UN1263
14.2. UN proper shipping name	Paint
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	II
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number	UN1263
14.2. UN proper shipping name	Paint
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	II
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number	UN1263
14.2. UN proper shipping name	Paint
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	II
14.5. Environmental hazards	No.
ERG Code	3H
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

- 14.1. UN number UN1263
14.2. UN proper shipping name Paint
14.3. Transport hazard class(es)
Class 3
Subsidiary risk -
Label(s) 3
14.4. Packing group II
14.5. Environmental hazards
Marine pollutant No.
EmS F-E,S-E
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code Not established.

ADN; ADR; IATA; IMDG; RID



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended
Not listed.
- Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended
Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended
Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended
Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended
Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended
Not listed.
- Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended
Not listed.
- Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA
Not listed.

Authorisations

- Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended
Not listed.

Restrictions on use

- Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended
ETHYL BENZENE (CAS 100-41-4)
Toluene (CAS 108-88-3)
AROMATIC PETROLEUM DISTILLATES (CAS 64742-95-6)
Mineral spirits (CAS 8052-41-3)
- Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.
AROMATIC PETROLEUM DISTILLATES (CAS 64742-95-6)

Mineral spirits (CAS 8052-41-3)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ETHYL BENZENE (CAS 100-41-4)

N-Butyl Alcohol (CAS 71-36-3)

Toluene (CAS 108-88-3)

XYLENE (CAS 1330-20-7)

Other regulations

Pregnant women should not work with the product, if there is the least risk of exposure. The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

Follow national regulation for work with chemical agents. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

Not available.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R10 Flammable.
R11 Highly flammable.
R20 Harmful by inhalation.
R20/21 Harmful by inhalation and in contact with skin.
R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
R21/22 Harmful in contact with skin and if swallowed.
R22 Harmful if swallowed.
R36/38 Irritating to eyes and skin.
R37/38 Irritating to respiratory system and skin.
R38 Irritating to skin.
R41 Risk of serious damage to eyes.
R45 May cause cancer.
R46 May cause heritable genetic damage.
R48/208 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R63 Possible risk of harm to the unborn child.
R65 Harmful: may cause lung damage if swallowed.
R67 Vapours may cause drowsiness and dizziness.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer by inhalation.
H351 Suspected of causing cancer.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Revision information

Product and Company Identification: Product Uses
Physical & Chemical Properties: Multiple Properties
Transport Information: Material Transportation Information

Training information

Follow training instructions when handling this material.

Disclaimer

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create any warranty, expressed or implied. It is the responsibility of the user to determine the applicability of this information and the suitability of the material or product for any particular purpose.